



BENETEAU

First 44

Provisional Specifications - Europe



First 44 Performance



sean@apps

CONNECT YOUR BOAT FREE YOUR MIND

GENERAL SPECIFICATIONS *

• L.O.A		
- First 44	14,15 m	46'5"
- First 44 Performance	14,65 m	48'1"
• Hull length	13,17m	43'2"
• L.W.L.	12,82 m	38'5"
• Beam	4,25 m	13'11"
• Standard draft (Cast iron)	2,15 m	7'1"
• Standard ballast weight (Cast iron)	3 300 kg	7,275 lbs
• Performance draft (Cast iron / Lead)	2,60 m	8'6"
• Performance ballast weight (Cast iron / Lead)	3 000 kg	6,612 lbs
• Air draft		
- Aluminum mast version	20,57 m	67'6"
- Carbon mast version	22,17 m	72'9"
• Light displacement	10 500 kg	23,142 lbs
• Fuel capacity (standard)	200 L	53 US Gal
• Fresh water capacity	720 L	190 US Gal
- First 44 (standard)	370 L	98 US Gal
- First 44 (option)	200 L	53 US Gal
- First 44 Performance	240 L	63 US Gal
• Engine power:		
- Sail drive (standard)	57 CV	57 HP

ARCHITECTS / DESIGNERS

- Naval Architect: BISCONTINI YACHT DESIGN
- Outside & interior design: LORENZO ARGENTO

EC CERTIFICATION *

- Category A - 12 people
- Category B - 12 people
- Category C - 14 people

STANDARD SAILS DIMENSIONS *

CLASSICAL MAST ALUMINUM

• Classic mainsail	53 m ²	942 sq/ft
• Genoa		
- Furler below deck	53 m ²	570 sq/ft
- Furler under deck	50 m ²	539 sq/ft
• Code 0	95 m ²	1,022 sq/ft
• Asymmetric spinnaker	170 m ²	1,830 sq/ft
• I	18,50 m	72'
• J - Furler below deck	5,98 m	21'
• J - Furler under deck	5,60 m	21'
• P	17,75 m	72'2"
• E	5,50 m	22'4"

CARBON CLASSICAL MAST (+ 1 m / 3'3")

• Classic mainsail	61 m ²	942 sq/ft
• Genoa		
- Furler below deck	56 m ²	603 sq/ft
- Furler under deck	60 m ²	646 sq/ft
• Code 0	105 m ²	1,130 sq/ft
• Asymmetric spinnaker	207 m ²	2,228 sq/ft
• I	18,50 m	72'
• J - Furler below deck	5,98 m	21'
• J - Furler under deck	5,60 m	21'
• P	17,75 m	72'2"
• E	5,50 m	22'4"

* Provisional specifications, boat in process of certification.

**STANDARD EQUIPMENT****CONSTRUCTION**

- Design in accordance with European Directive requirements and according to CE certification
- ISO 12215 certified structure
- Balsa sandwich infusion hull
- Vacuum infused structural inner liner (Fabrics - resin) bonded to the hull
- Fiberglass sandwich, PET foam, balsa wood infusion deck, with diamond pattern non-slip coating
- Cast iron keel attached with bolts and bonded stainless steel backplate
- Polyester bowsprit, 1,00m / 3'3"
- Twin rudders hung with stainless steel stock
- White coloured hull - Aluminum grey hull decoration
- 6 Hull portholes

DECK EQUIPMENT**RIGGING**

- **Anodized aluminum classical mast** tapered, deck stepped, 2 Aft swept spreaders, Sparcraft,
 - C-strand Rigging,
 - Stainless steel split backstay with manual hydraulic piston to starboard (hydraulic unit optional),
 - Harken Element blocks at foot of mast,
 - Facnor mainsail track (without traveller),
 - Aluminum boom with LED lighting (warm white)
- **Carbon classical mast** tapered, deck-stepped (+1,60m / 5'3", Weight saving: 75kg / 165 lbs) 3 Aft swept spreaders,
 - ROD standing rigging,
 - Stainless steel split backstay with manual hydraulic piston to starboard, Sparcraft,
 - Harken blocks at foot of mast,
 - Harken System A mainsail track (without traveller),
 - Black lacquered aluminium Racing boom with LED lighting (warm white)
- Black lacquered aluminum rigid kicking strap with Dyneema tackle and friction rings
- Genoa tracks on the roof with traveller and hauling line controlled from the cockpit
- Manual Genoa furler on the deck (Facnor Flatdeck)
- 1 mainsail attachment point at bottom of cockpit with 1 stand-up block
- German system (Two-way mainsheet at the helm station)
- All lines brought back to the helm stations (except boom topping lift)
- Dyneema Complete running rigging:
 - Mainsheet halyard sheave block,
 - Genoa halyard,
 - Boom uphaul (polyester) with cleat on mast,
 - Mainsheet,
 - 2 Genoa sheets,
 - 2 Automatic reefing system
- 8 halyard clutches to port, 4 to starboard
- Harken blocks
- 2 Spinnaker sheet chain plates/code 0
- Running rigging hidden
- Lazy jacks
- 2 Flag halyards

WINCHES (First 44)

- 2 H46.2 STA manual self-tailing manoeuvre winches (at helm stations)
- 2 H50.2 STA manual self-tailing genoa winches (at helm stations)
- 2 Aluminum Speed Grip winch handles

SAILS

- Boast supplied without sail - Available as option

FIRST 44 PERFORMANCE VERSION

(compatible with standard mast, black lacquered aluminium 2 aft swept spreaders mast and carbon mast, compatible with both keels)

- 1.5 m / 4'11" carbon bowsprit (in lieu of standard)
- Mainsail Cunningham
- Mainsail traveller at bottom of cockpit (instead of single point of attachment)
- 2nd genoa halyard
- Harken Carbo racing dual-groove head foil instead of the flat deck furling system
- 8:1 barber hauler
- Downwing Pack (2 HARKEN Black Magic blocks for the spinnaker/code 0 sheet, 1 HARKEN Black Magic block for the spinnaker tack led back to the dedicated cleat in the cockpit, 1 Dyneema halyard sheave with block for spinnaker or code 0, 1 Dyneema halyard for spinnaker, Barber hauler with blocks and chainplate on bulwark, 1 spinnaker tack led back to dedicated cleat in the cockpit, barber-hauler, short sheet pad eye)
- 1 Wichard double chainplate on forward deck for removable forestay, 1 Dyneema halyard sheave with block for staysail
- Cockpit sole, benches, platform with synthetic foam coating (light grey color)
- White gel-coat, Aluminum grey hull decoration, white decoration film layer on cabins hull porthole

Winches - HARKEN Performa

- 2 H50.2 STP Harken Performa manual manoeuvre winches on the roof + 3 clutches on port and starboard roof
- 2 H60.2 STP Harken Performa manual genoa winches behind cockpit benches
- 2 H50.2 STP Harken Performa manual Spinnaker winches with blocks - cleats - jib halyard (for mainsail sheet, adjustment genoa traveller - staysail sheet- boom vang - mainsail tack + 1&2 reef - and for spinnaker tack - barber hauler
- 4 Aluminum Speed Grip winch handles
- Winch handle storage in dedicated space in rope bags

Other specificities of the PERFORMANCE version

- No windlass
- No bow roller
- No helm consoles for better access to the
- mainsail traveller on cockpit sole
- No side access gates
- No HiFi equipment (Fusion/speakers)
- No courtesy lighting on side decks
- Fresh water tank limited to 220L / 53 US Gal and positioned aft to starboard for a better distribution of weight aboard (in lieu of 330L / 87 US Gal)
- 1 200Ah Lithium battery to replace the AGM batteries - Weight saving: Approximately 110 kg / 242 lbs
- 3 Lee cloth (Saloon & Aft cabins)



MOORING LINES - MOORING

- Polyester bowsprit (1,00 m / 3'3") with integrated anchoring gear and bobstay with spinnaker chainplate (for Code 0 and asymmetric spinnaker) (First 44 version)
- Self-draining chain locker, Clench bolt, Piston, Cover (First 44 version)
- Single roller stainless steel bow fitting (First 44 version)
- 12 V - 1 000 W vertical electrical windlass - Remote control in mooring locker (First 44 version)
- 6 Anodised aluminum mooring cleats (Length: 0,30m / 12")
- Stainless steel chafing plate

SAIL LOCKER

Access through piston-driven cover

- LED lighting

SAFETY ON DECK

- 1 Stainless steel open pulpit
- 2 Stainless steel aft pulpits with integrated fairlead
- 1 Stainless steel central aft pulpit (Height: 960mm / 3'2")
- 2 Stainless steel handrails on the roof
- 1 Lifebuoy support bracket on aft pulpit
- Wooden flagstaff (1 m/3'3") with integrated support on pushpit
- Dual stainless steel lifelines and stainless steel stanchions (Height: 620mm / 2') - Side boarding gate on either side (First 44 version)
- Emergency ladder on pushpit

COCKPIT

- Self-draining cockpit
- Slatted teak (First 44 version)
- 2 Sail lockers below cockpit seating
- 1 Access hatch to tender garage
- 1 Diesel deck filler at the aft of the side deck
- 1 Shore power socket in port side storage
- 1 Water deck filler located on forward roof on side deck
- 1 Gas locker in the bottom of the cockpit
- Slatted teak cockpit benches (First 44 version)
- Slatted teak side helmsman's seat (First 44 version)
- Foldaway helmsman foot chock
- 2 Steering wheel consoles with stainless steel handrail (First 44 version)
- Black composite helm (diameter 900 mm / 2'11") fixed on white lacquered aluminum pedestal
 - Steering gear at the helm station
 - Stainless steel steering chain transmission system
- 1 Emergency tiller
- 1 Steering compass on port console
- Mechanical engine throttle and control panel on starboard
- 1 Cockpit shower with mixer tap in the tender garage
- 1 PPMA folding companionway door in the bottom of the cockpit - Sliding hatch made of PMMA
- Liferaft locker in front of the companionway (Usable dimensions: 0,93 m x 0,59 m x 0,33 m / 3'1" x 1'11" x 1'1")
- Courtesy lighting (6 LED lighting points, warm white lighting) (First 44 version)

SWIM PLATFORM / AFT TRANSOM

- Fully opening transom, convertible to bathing platform (2,32 m x 0,67 m / 7'7" x 2'2")
- 1 Folding access step to the cockpit to starboard
- Manual opening
- Slatted teak on swim deck (First 44 version)
- 1 Stainless steel removable bathing ladder (dedicated storage in starboard cockpit locker)

TENDER GARAGE

Accessible from the platform and from the cockpit

Can be used to house a Highfield Roll-Up type tender (2m / 6'7")

- 1 Touch-operated ceiling LEDs



INTERIOR

- Alpi teak woodwork and white lacquered wood on bulkheads
- Alplikord teak flooring
- Lounge Falcon 162 fabric interior upholstery
- Mattresses in the cabins (HR foam 35 kg/m³, thickness 120 mm/5")
- Beige padded ceilings

Standard version: 3 cabins + 2 heads



COMPANIONWAY

Headroom: 1,98 m / 6'6"

- Saloon companionway with 5 suspended Alplikord teak non-slip steps, LED lighting below each step
- 1 Leather-covered stainless steel handrail (DK02 - chocolat color)

SALOON

Headroom: 1,95 m / 6'5"

Port saloon

- Alpi teak saloon table with fixed top (can seat up to 6 diners)
- Face to face benches with large storages under seat
- Face to face saloon convertible into double berth as option

Starboard saloon

- Comfortable sofa facing the saloon:
 - seats with HR26 and HR30 foam
 - softness thanks to the finish with hollow fibres + padding
 - storages under seats
- 1 230 V socket
- 1 Electrical panel to starboard incorporated into a high cabinet

- 2 T44 Opening deck hatches with mosquito screen/blinds
- Indirect LED lighting below the soft and the upper part of the portholes
- 1 Adjustable reading light
- Pillar with beige cover

CHART TABLE

- At starboard of companionway
- Long chart table with fiddles, storage under the lifting top
- High cabinet with storage (or, in option, navigation screen)
- 1 Adjustable reading light
- 1 dual USB port
- 1 230 V socket

GALLEY - PORT

Headroom: 1,92m / 6'4"

- L-shaped galley
- Corian Glacier White work top with moulded Apli teak beading
- 1 1 rectangular stainless steel sink - 1 Mixer tap with hot/cold water under pressure
- 1 Gas cooker 2 burners - Stainless steel/grill fitted on swivel joints (19L) - Stainless steel protection handrail - Stowage below the oven with drop-down door
- 1 storage unit with 1 door and 1 internal drawer for cutlery
- 190L / 50 US Gal icebox, with top and front opening
- Fitted lockers and closed shelving
- 1 Bin (20L)
- 1 Opened compartment along the side of the hull
- 1 Opening porthole on coaming in side window

OWNER'S CABIN

Headroom: 2,01 - 1,96m / 6'7" - 6'5"

- Central double bed (2,00m x 1,60m - 1,15m / 6'9" x 5'3" - 3'9")
- Padding along the hull and at headboard: Beige PVC
- 1 Bed access sideboard
- 1 Chair on each side of bed
- 1 Hanger closet, with incorporated LED lighting
- 2 Flexible and adjustable bedside lamps
- 1 T60 flush deck hatch with blind/mosquito net
- 1 Opening flush deck hatch (330 mm x 140 mm)
- 2 Hull portholes with rigid sliding blind
- 1 230 V power socket to starboard
- 1 dual USB port outlet on each side of the bed
- LED indirect lighting + 2 overhead lights

1 PRIVATE HEAD

to port

Headroom: 1,92m / 6'4"

- 1 Shower with foldable perspex door
- 1 Manual toilet
- 1 64 L / 17 US Gal rigid holding tank
- Work top in Corian Glacier White
- 1 Integrated polyester basin - Mixer tap
- 1 Cabinet - Mirror
- Toilet accessories
- 1 Deck hatch with opaque film
- LED indirect lighting + Spot lighting

PORT AND STARBOARD AFT CABIN

Headroom: 1,92m / 6'4"

- 1 Double bed (2,04 m x 1,38 m / 6'8" x 4'6")
- 1 Hanging locker, 1 Cupboard with shelves, with incorporated LED lighting
- 1 Top-opening storage in front of the wardrobe
- 1 Opened compartment along the side of the hull
- 2 Flexible and adjustable reading lights
- 1 dual USB port
- 1 230 V socket
- 1 Porthole with rigid sliding blind
- 1 Opening window below cockpit seat with pleated blind
- 1 Opening windows on coaming with pleated blind

AFT STARBOARD HEAD COMPARTMENT

Headroom: 1,93m / 6'4"

Access from the saloon

- Shower separated with a perspex door - 1 Mixer tap - White polyester shower base
- Corian Glacier White work top
- 1 Manual toilet
- 1 64L / 17 US Gal rigid holding tank
- 1 Washbasin - 1 Mixer tap
- 1 Cabinet + Storage space under the basin
- 1 Mirror
- Toilet accessories
- 1 Opening porthole on coaming in side window, opaque film, mosquito screen
- LED indirect lighting + 1 overhead light



ENGINE

- Engine Yanmar Diesel:
 - 57 HP, Sail Drive, Common Rail (standard)
- Engine control at the starboard helm station - Control panel
- Engine compartment:
 - Soundproofing foam
 - Ventilation: 2 air intakes and 1 forced air outlets
- 1 Alternator (12V / 125Ah)
- 1 Rotomoulded diesel tank 200L / 53 US Gal (under aft berth port) - Electronic gauge - Low level alarm - 1 Deck filler
- Filters: Seawater - Diesel - Water separator
- Foldable three-blade propeller
- 1 Engine access through companionway (opening with 2 gas struts)
- 2 Engine access through aft cabins

PLUMBING

- 1 Rotomoulded freshwater tank 330L / 87 US Gal, under berth in forward cabin - 1 Deck filler
- Pressurised electric water pump - Expansion tank - Inline filter
- 40 L / 11 US Gal Electric water heater (engine use)
- 1 Rigid black water holding tank for each WC
- Electrical shower drain pumps
- 1 Electric bilge pump
- 1 Manual bilge pump

GAS

- 1 Box for 2 gas bottles in the anchor locker (Diameter: 0,39 x 039m / 1'3" x 1'3" x Height: 0,51m / 1'8")
- Regulator and safety tap
- Gas leak detector

SMART BOARD

"SEANAPPS" smart technology:

- For monitoring the boat's status and receiving alerts as well as maintenance advice via the associated mobile application.
- The type of information collected (GPS position, batteries, engine info, navigation data, etc.) varies according to the boat's configuration.

seanapps

CONNECT YOUR BOAT FREE YOUR MIND

ELECTRICITY

- 12V electrical panel (Breaker, Voltmeter, Water gauge, Fuel gauge, Battery warning, Fuel warning, Water warning) + single USB port + Navicolor 2.4" screen
- 12V circuit
- 2 AGM service batteries (100Ah)
- 1 AGM engine battery (50Ah)
- Battery cut-off switch in the aft starboard cabin (under bed)
- 1 Battery charger (40Ah)
- 1 Power distributor
- 5 230V Sockets:
 - 1 in the forward cabin
 - 1 in the aft cabins
 - 1 in the saloon (Starboard)
 - 1 at chart table
 - 1 in galley
- 6 USB socket:
 - 2 in the forward cabin
 - 1 in the aft cabins
 - 1 on the electrical panel
 - 1 at chart table
- 1 Shore power socket 230 V, in the port cockpit locker
- LED lighting:
 - Overhead lights
 - Reading lights
 - Indirect lighting
- LED navigation lights:
 - 1 Masthead light
 - 1 Steaming light
 - 1 Anchor light on masthead

MISCELLANEOUS ITEMS

- Smoke detector

**TRIM LEVEL & PACKS****TRIM LEVEL (First 44)**

	CONFORT	LUXE
<ul style="list-style-type: none"> Coastal Pack (GARMIN) Windlass control in cockpit with chain counter Retractable bow thruster + 2 Dedicated batteries (50 Amps - 12V) - Control on starboard console HiFi: RA210 Fusion + 2 Interior loudspeakers & 2 Waterproof exterior speakers Induction charging station for smartphones at the chart table Cabins: Mosquito nets for opening portholes LED indirect lighting 3,5" Navicolor screen, Battery charge display IBS sensor 2 Additional 140 ampères service batteries 	<ul style="list-style-type: none"> ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ 	<ul style="list-style-type: none"> ■ ■ ■ ■ ■ ■ ■ ■ ■ ■
<ul style="list-style-type: none"> Offshore Pack (GARMIN) Electrical opening bathing platform, Control at the helm station + Remote control 1 Solid wood cockpit table on stainless steel pedestal, 2 extension leaves, 1 opened central storage + Protective cover (Cadet Grey) Spring mattress in the owner's cabin (thickness: 180mm / 7") TECMA electric fresh water/sea water WC in the owner's head Quiet Flush fresh water/seawater electric WC in the aft starboard head Electrical engine control on the starboard console 		<ul style="list-style-type: none"> ■ ■ ■ ■ ■ ■ ■

ELECTRONICS PACKS: GARMIN**Garmin Packs (First 44)**

	COASTAL (included in the Confort trim level)	OFFSHORE (included in the Luxe trim level)
<ul style="list-style-type: none"> Port and starboard helm stations: <ul style="list-style-type: none"> Steering wheel console 1 12" GPS Map 1223 multi-function touchscreen (GPS, Chart plotter, Card reader - Bluechart G3 cartography included) Wind Sensor gWind Race - pole 1 m/3'3": Windvane, Anemometer Airmar DST810 sensor (Log, Speedometer, Temperature) PC interface (GND10) Fixed 315i VHF at chart table, without AIS receiver function Windex Windvane Protective covers for helm & consoles (Charcoal Grey) 	<ul style="list-style-type: none"> ■ ■ ■ ■ ■ ■ ■ 	<ul style="list-style-type: none"> ■ ■ ■ ■ ■ ■ ■
<ul style="list-style-type: none"> Reactor 40 Pilot with GHC50 control on port console (LS40 hydraulic unit drive) Wireless autopilot remote control Garmin Quatix 7 connected watch 		<ul style="list-style-type: none"> ■ ■ ■

FASTNET PACK (REQUIRES THE COASTAL OR OFFSHORE PACK)

- 3 GNX120 7" mast screens + mast bracket + cover
- AIS 800
- GHS11 VHF Wired handset at starboard helm station

Garmin Pack (First 44 Performance)**PERFORMANCE PACK (without console at helm station)**

- 3 GNX120 7" mast screens + mast bracket + cover
- AIS 800
- Garmin Quatix 7 connected watch
- Wind Sensor gWind Race - pole 1 m/3'3": Windvane, Anemometer
- PC interface (GND10)
- Airmar DST810 sensor (Log, Speedometer, Temperature)
- Fixed 315i VHF at chart table, without AIS receiver function
- GHS11 VHF Wired handset at starboard helm station
- Windex Windvane
- Protective covers for steering wheels (Charcoal Grey)

**RIGGING PACKS**

For First 44 version:**DOWNWIND PACK (Compatible with the 3 masts)**

- 2 HARKEN Black Magic blocks for spinnaker sheet/code 0
- 1 HARKEN Black Magic block for spinnaker tackline with return on dedicated cleat in cockpit
- 1 Dyneema sheaved halyard with block for spinnaker or code 0
- Barber hauler with blocks and chain plate on bulwark

SELF-TACKING JIB RIGGING PACK (Compatible with all masts and all rigging packs)

- Self-tacking jib hardware (sheet only) - 3 blocks
- 1 Self-tacking jib track with traveller

SELF-TACKING STAYSAIL RIGGING PACK (Compatible with the 3 masts - requires the self-tacking jib rigging pack)

- 1 Wichard double chainplate on forward deck for removable forestay
- 1 Dyneema halyard sheave with block for staysail

ALUMINIUM MAST SAILS PACK - NORTH SAILS

- Full batten mainsail (53 m² / 570 sq/ft) and Genoa (50 m² / 539 sq/ft or 60m² / 646 sq/ft depending on furler) North Sails NPL tour, dark grey
- Charcoal Grey lazy bag

CARBON MAST SAILS PACK - NORTH SAILS

- Full batten mainsail (61m² / 657 sq/ft) and Genoa (56m² / 603 sq/ft or 53 m² / 570 sq/ft depending on furler) North Sails NPL tour, dark grey
- Charcoal Grey lazy bag

MOORING PACK

- Delta 20 kg / 44 lbs anchor (galvanized steel)
- Chain (Diameter: 10mm / $\frac{3}{8}$ " - Length: 32m / 105')
- Line (Diameter: 18mm / $\frac{11}{16}$ " - Length: 45m / 147')
- 6 Fenders:
 - 4 XL (Diameter: 300mm / 12" - Length: 880mm / 2'11")
 - 2 L (Diameter: 250mm / 10" - Length: 700mm / 2'4")
- 4 Moorings lines (Diameter: 18mm / $\frac{11}{16}$ " - Length: 15m / 49'3")

Compatible with First 44 and Firt 44 Performance version:**BLACK EDITION PACK**

- 6 Black anodised aluminum mooring cleats (Length: 0,40m / 1'4")
- Black lacquered stainless steel pulpits, handrails, stanchions
- Textile lifelines with side boarding gates (First 44 performance without side boarding gates)



OPTIONS

NAVIGATION ELECTRONICS: GARMIN _____

First 44

- Chart table: 12" GPS Map 1223 multi-function touchscreen
- AIS 800
- Panoptix PS51-TH (Forward underwater vision)
- Phantom 18x radar
- GHS11 VHF Wired handset at port helm station

RIGGING - SAILS _____

For First 44 version:

- Manual genoa furler below deck
- Aluminum black lacquered canoe boom, Sparcraft, Integrated LED lighting for the cockpit area
- Code 0 with North Sails Xi06 TF1,FX 4500 Facnor furler, dark grey laminated: 95 m² / 1,022 sq/ft (for aluminum mast)
- Code 0 with North Sails Xi06 TF1,FX 4500 Facnor furler, dark grey laminated: 105 m² / 1 023 sq/ft (for carbon mast)

Compatible with First 44 and Firt 44 Performance version:

- Black lacquered aluminum classical mast
- Harken Hydraulic unit (compatible with the 3 masts): Hydraulic textile backstay on piston, 1 speed

WINCHES _____

First 44

- 1 Electric manoeuvre winch to port - H50.2 STAEH in lieu of standard
- 1 Electric manoeuvre winch to starboard - H50.2 STAEH in lieu of standard
- Upgrade for manual genoa winches: H60.2 STA replacing standard manual H50.2 STA
- 2 Electric Harken genoa sheet winches (H60.2 STPEH), replacing standard manual H50.2 STA

First 44 Performance

- Upgrade : 2 Winches électriques de manoeuvre Harken Performa (H60.2 STPEH)

HULL - DECK - COCKPIT _____

For First 44 version:

- Pearl grey gel-coat (Hull & Bowsprit), hull decoration white pearl
- Metallic hull paint (Hull, Aft transom, Bowsprit)
- Slatted teak catwalks
- Slatted teak roof
- LED lighting of spreaders, for anodized aluminium mast, black lacquered aluminum mast, carbon mast
- Retractable bow thruster (Side Power 185 80 12)

Compatible with First 44 and Firt 44 Performance version:

- White composite steering wheels
- Outboard engine bracket
- Polyester folding gangway (2,60m / 8'6")
- Electric inflator/deflator for tender and fenders (portable, battery-powered)
- Shore fresh water supply
- 1,20 m/3'11" carbon flagstaff (in lieu of standard)

COCKPIT COMFORT - First 44

- Outside cockpit upholstery with backrests, Filter foam 80 mm/3" thickness (Density: 60F + 20S):
 - Sunbrella Terry beige
 - Dolce 51

OUTSIDE PROTECTIONS - First 44

- Sprayhood with LED lighting, Strataglass windows, Charcoal Grey
- Bimini Charcoal Grey (sprayhood option required)
- Sunshade for the cockpit, Charcoal Grey (compatible with all booms)

INTERIOR EQUIPMENT _____

AMBIANCE

- Interior upholstery according to colour chart: Fabrics, Leather, Nubuck, Ultraleather

DOMESTIC APPLIANCES

- 1 3 burners ENO Grand Large Gas cooker + Tempered glass cover on the hotplate

ON BOARD COMFORT EQUIPMENT

For First 44 version:

- Air conditioning 16 000 BTU in saloon and forward cabin
 - + Pre-fitting in aft cabins (+ Shore socket extension cord 15m / 49'3") - 32A
- Forced air heating fuel
- Berth in saloon (Electric saloon table pedestal + cushion matching the saloon upholstery for Lounge area use)
- 12V / 230V inverter - 2 000 VA
- 1 200Ah Lithium batteries to replace the AGM batteries - Weight saving: Approximately 110 kg / 242 lbs

The lithium batteries can be used in exactly the same way as the greater number of AGM batteries that they replace. This technology allows 100% of the battery capacity to be used compared with 75% for the AGM batteries. The engine battery is still AGM.
- Additional water tanks (200 L / 53 US Gal), under aft starboard cabin berth

Compatible with First 44 and Firt 44 Performance version:

- Air conditioning 16 000 BTU in saloon and forward cabin
 - (+ Shore socket extension cord 15m / 49'3") - 32A
- Seawater electric pump, in galley